



MATERIAL SAFETY DATA SHEET

Section 1: Product & Company Identification

Product Name: Ice-Off® Windshield Spray De-Icer (aerosol)

Product Number (s): 05346

Product Use: melt ice on windshields

Manufacturer / Supplier Contact Information:

In United States:

CRC Industries, Inc.

885 Louis Drive

Warminster, PA 18974

www.crcindustries.com

1-215-674-4300 (General)

(800) 521-3168 (Technical)

(800) 272-4620 (Customer Service)

In Canada:

CRC Canada Co.

2-1246 Lorimar Drive

Mississauga, Ontario L5S 1R2

www.crc-canada.ca

1-905-670-2291

In Mexico:

CRC Industries Mexico

Av. Benito Juárez 4055 G

Colonia Orquídea

San Luís Potosí, SLP CP 78394

www.crc-mexico.com

52-444-824-1666

24-Hr Emergency – CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

DANGER: POISON. Flammable. Vapor Harmful. May be Fatal or Cause Blindness if Swallowed. Contents Under Pressure.

Appearance & Odor: Colorless liquid, characteristic pungent odor

Potential Health Effects:

ACUTE EFFECTS:

EYE: May cause mild irritation. Symptoms include stinging, tearing, and redness.

SKIN: May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, and may add to toxic effects from breathing or swallowing.

INHALATION: Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful, and may cause irritation of airways, dizziness, drowsiness, nausea, and vomiting.

INGESTION: Swallowing this material may be harmful. Symptoms may include nausea, vomiting, dizziness, leg cramps, pain in the abdomen or lower back, blurred vision, shortness of breath, visual impairment (including blindness), coma and death.

CHRONIC EFFECTS: Overexposure to this material may cause liver abnormalities, central nervous system damage, and visual impairment.

TARGET ORGANS: Liver, kidneys, pancreas, heart, lungs, and brain

Medical Conditions Aggravated by Exposure: Pre-existing disorders of the following organs: Skin, lung, liver, kidney central nervous system, pancreas, and heart.

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Methanol	67-56-1	85 - 95
Water	7732-18-5	3 - 8
Propylene glycol	57-55-6	< 1
Carbon dioxide	124-38-9	5 - 10

Section 4: First Aid Measures

- Eye Contact:** Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.
- Skin Contact:** Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.
- Inhalation:** Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.
- Ingestion:** Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Note to Physicians: Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 µg/dl. Methanol is effectively removed by hemodialysis. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and may be used as an antidote in the treatment of methanol poisoning.

Section 5: Fire-Fighting Measures

Flammable Properties: This product is flammable in accordance with aerosol flammability definitions. (See 16 CFR 1500.3(c)(6)).

Flash Point:	54°F / 12°C (TCC)	Upper Explosive Limit:	36
Autoignition Temperature:	725°F / 385°C	Lower Explosive Limit:	7.3

Fire and Explosion Data:

Suitable Extinguishing Media: Dry chemical, alcohol-resistant foam, carbon dioxide (CO₂)

Products of Combustion: Carbon dioxide and carbon monoxide

Explosion Hazards: Aerosol containers, when exposed to heat from fire, may build pressure and explode. Vapors may accumulate in a confined space and create a flammable atmosphere.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains. If run-off occurs, notify the proper authorities as required, that a spill has occurred.

Methods for Containment & Clean-up: Eliminate all ignition sources. Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For product use instructions, please see the product label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120°F / 49°C to prevent cans from rupturing.

Aerosol Storage Level: III

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Methanol	200	NE	200 (s)	250 (s)	NE	NE	ppm
Water	NE	NE	NE	NE	NE		
Propylene glycol	NE	NE	NE	NE	10	AIHA	mg/m ³
Carbon dioxide	5000	30000(v)	5000	30000	NE		ppm
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile or natural rubber. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid
 Color: colorless
 Odor: characteristic pungent odor
 Odor Threshold: ND
 Specific Gravity: 0.809
 Initial Boiling Point: 148.5°F / 65°C
 Freezing Point: ND
 Vapor Pressure: 16.93 kPa @ 77°F / 25°C
 Vapor Density: 1.1 (air = 1)
 Evaporation Rate: fast
 Solubility: completely soluble in water
 Coefficient of water/oil distribution: ND
 pH: NA
 Volatile Organic Compounds: wt %: 87.8 g/L: 710.3 lbs./gal: 5.92

Section 10: Stability and Reactivity

Stability: Stable
 Conditions to Avoid: Sources of ignition
 Incompatible Materials: Hypochlorites, peroxides, reactive metals such as aluminum and magnesium,, sodium, strong acids, strong bases, strong oxidizing agents, zinc
 Hazardous Decomposition Products: Carbon dioxide and carbon monoxide
 Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

<u>Component</u>	<u>Oral LD50 (rat)</u>	<u>Dermal LD50 (rabbit)</u>	<u>Inhalation LC50 (rat)</u>
Methanol	5628 mg/kg	15,800 mg/kg	64,000 ppm/4H
Water	> 90 mL/kg	No data	No data
Propylene glycol	20 g/kg	20,000 mg/kg	4.1 mg/L/8H
Carbon dioxide	No data	No data	470,000 ppm/30M

Chronic Toxicity:

<u>Component</u>	<u>OSHA Carcinogen</u>	<u>IARC Carcinogen</u>	<u>NTP Carcinogen</u>	<u>Irritant eye, skin</u>	<u>Sensitizer Unknown</u>
Methanol	No	No	No	No	No
Water	No	No	No	No	No
Propylene glycol	No	No	No	No	No
Carbon dioxide	No	No	No	No	No

<u>Reproductive Toxicity:</u>	No information available
<u>Teratogenicity:</u>	No information available
<u>Mutagenicity:</u>	No information available
<u>Synergistic Effects:</u>	No information available

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity:	No information available
Persistence / Degradability:	No information available
Bioaccumulation / Accumulation:	No information available
Mobility in Environment:	No information available

Section 13: Disposal Considerations

Waste Classification: The dispensed liquid product is a RCRA hazardous waste for the characteristic of ignitability with the following potential waste codes: D001, U154. (See 40 CFR Part 261.20 – 261.33) Empty aerosol containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

Section 14: Transport Information

US DOT (ground):	UN1950, Aerosols, flammable, 2.1, Limited Quantity**
ICAO/IATA (air):	UN1950, Aerosols, flammable, 2.1, Limited Quantity
IMO/IMDG (water):	UN1950, Aerosols, 2.1, Limited Quantity
Special Provisions:	**This product can be classified and labeled as 'Consumer Commodity, ORM-D' for domestic ground shipping until January 1, 2014. If shipping as limited quantity by ground, note that shipping papers are not required.

Section 15: Regulatory Information

U.S. Federal Regulations:

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: Methanol (5000 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:	Fire Hazard	Yes
	Reactive Hazard	No

Release of Pressure	Yes
Acute Health Hazard	Yes
Chronic Health Hazard	No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
Methanol (<88%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): Methanol

Occupational Safety and Health Administration (OSHA):

This product is regulated under the Hazard Communication Standard.

U.S. State Regulations:

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: None

Consumer Products VOC Regulations: None

State Right to Know:

New Jersey: 67-56-1, 57-55-6, 124-38-9
Pennsylvania: 67-56-1, 57-55-6, 124-38-9
Massachusetts: 67-56-1, 57-55-6, 124-38-9
Rhode Island : 67-56-1, 57-55-6, 124-38-9

Canadian Regulations:

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: A, B5, D2B

Canadian DSL Inventory: All ingredients are either listed on the DSL Inventory or are exempt.


European Union Regulations:

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003. This product does not contain any of the restricted substances as listed in Article 4(1) of the RoHS Directive.

Additional Regulatory Information: None

Section 16: Other Information

HMIS® (II)	
Health:	1
Flammability:	3
Reactivity:	0
PPE:	B



Ratings range from 0 (no hazard) to 4 (severe hazard)

Prepared By: Michelle Rudnick
 CRC #: 638
 Revision Date: 11/02/2012

Changes since last revision: MSDS reformatted to meet the requirements of the Canadian Controlled Products Regulations.

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

ACGIH: American Conference of Governmental Industrial Hygienists
 CAS: Chemical Abstract Service
 CFR: Code of Federal Regulations
 DOT: Department of Transportation
 DSL: Domestic Substance List
 g/L: grams per Liter
 HMIS: Hazardous Materials Identification System
 IARC: International Agency for Research on Cancer
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 IMDG: International Maritime Dangerous Goods
 IMO: International Maritime Organization
 lbs./gal: pounds per gallon
 LC: Lethal Concentration
 LD: Lethal Dose

NA: Not Applicable
 ND: Not Determined
 NIOSH: National Institute of Occupational Safety & Health
 NFPA: National Fire Protection Association
 NTP: National Toxicology Program
 OSHA: Occupational Safety and Health Administration
 PMCC: Pensky-Martens Closed Cup
 PPE: Personal Protection Equipment
 ppm: Parts per Million
 RoHS: Restriction of Hazardous Substances
 STEL: Short Term Exposure Limit
 TCC: Tag Closed Cup
 TWA: Time Weighted Average
 WHMIS: Workplace Hazardous Materials Information System